

Concluded
99

than the resistance of another electric current flow path B extending between the electroconductive member and the ground by way of the electron source or the drive circuit.--

IN THE CLAIMS:

Please cancel Claims 1, 2, 7, 8, 10, 12, 13, 24 and 25 without prejudice or disclaimer of the subject matter recited therein.

Please amend Claims 3, 4, 5, 9, 11, 14, 16-19, 21 and 22 as follows. A marked-up copy of the amended claims showing the changes made thereto, is attached. Note that all the claims currently pending in this application, including those not presently being amended, have been reproduced below for the Examiner's convenience.

1. Cancelled.

2. Cancelled.

Q10
B1

3. (Amended) An image-forming apparatus comprising

an envelope;

an electron source and an image-forming member arranged within said envelope;

an electron source drive circuit;

an electroconductive member arranged on an inner wall surface of said envelope between said electron source and said image forming member; and

an electric circuit flow path A extending between said electroconductive member and the ground passing through said electron source and said drive circuit, wherein

said electric current flow path A has a resistance lower than the resistance of another electric current flow path B extending between said electroconductive member and the ground by way of said electron source or said drive circuit, and

wherein said envelope carries an anti-charge film arranged on said inner wall surface thereof.

4. (Amended) An image-forming apparatus according to claim 1, wherein said anti-charge film is electrically connected to said electroconductive member.

5. (Amended) An image-forming apparatus comprising:
an envelope;
an electron source and an image-forming member arranged within said envelope;

an electron source drive circuit;
an electroconductive member arranged on an inner wall surface of said envelope between said electron source and said image forming member; and

an electric circuit flow path A extending between said electroconductive member and the ground passing through said electron source and said drive circuit, wherein

Amended
B10
B1

said electric current flow path A has a resistance lower than the resistance of another electric current flow path B extending between said electroconductive member and the ground by way of said electron source or said drive circuit, and

wherein said envelope carries an electroconductive film having a sheet resistance between $10^8 \Omega/\square$ and $10^{10} \Omega/\square$ on said inner wall surface thereof.

6. (Not Amended) An image-forming apparatus according to claim 5, wherein said electroconductive film is electrically connected to said electroconductive member.

7. Cancelled.

8. Cancelled.

Amended
B1

5. (Amended) An image-forming apparatus comprising:
an envelope;
an electron source and an image-forming member arranged within said envelope;
an electron source drive circuit;
an electroconductive member arranged on an inner wall surface of said envelope between said electron source and said image forming member; and
an electric circuit flow path A extending between said electroconductive member and the ground passing through said electron source and said drive circuit, wherein

Cancelled
Q4
B1

said electric current flow path A has a resistance lower than the resistance of another electric current flow path B extending between said electroconductive member and the ground by way of said electron source or said drive circuit, and wherein said electron source is entirely surrounded by said electroconductive member.

Cancelled

10. Cancelled.

Q12
B1

6 ~~11.~~ (Amended) An image-forming apparatus comprising:

an envelope;

an electron source and an image-forming member arranged within said envelope;

an electron source drive circuit;

an electroconductive member arranged on an inner wall surface of said envelope between said electron source and said image forming member; and

an electric circuit flow path A extending between said electroconductive member and the ground passing through said electron source and said drive circuit, wherein

said electric current flow path A has a resistance lower than the resistance of another electric current flow path B extending between said electroconductive member and the ground by way of said electron source or said drive circuit,

said electric current flow path A has a conductor terminal abutting against said electroconductive member, and

Cancelled
A12 B1

wherein said conductor terminal is drawn out of said envelope through
a substrate side thereof where said image-forming member is arranged.

- 12. Cancelled.
- 13. Cancelled.

A13

B1

7

~~14.~~

(Amended) An image-forming apparatus comprising:

an envelope;
an electron source and an image-forming member arranged within said
envelope;
an electron source drive circuit;
an electroconductive member arranged on an inner wall surface of said
envelope between said electron source and said image forming member; and
an electric circuit flow path A extending between said
electroconductive member and the ground passing through said electron source and said drive
circuit, wherein
said electric current flow path A has a resistance lower than the
resistance of another electric current flow path B extending between said electroconductive
member and the ground by way of said electron source or said drive circuit,
said image-forming member is arranged opposite to said electron
source and said electroconductive member is arranged on a substrate side of said envelope where
said electron source is arranged, and

Concluded
Q13
B1

said image-forming member has an accelerator electrode for accelerating the electrons emitted from said electron source and a voltage applying terminal of said accelerator electrode is drawn out of said envelope through a substrate side thereof where said electron source is arranged.

15. (Not Amended) An image-forming apparatus according to claim 14, wherein said electric current flow path A has a conductor terminal abutting against said electroconductive member.

Q14
B1

11 16. (Amended) An image-forming apparatus comprising:
an envelope;
an electron source and an image-forming member arranged within said envelope;
an electron source drive circuit;
an electroconductive member arranged on an inner wall surface of said envelope between said electron source and said image forming member; and
an electric circuit flow path A extending between said electroconductive member and the ground passing through said electron source and said drive circuit, wherein
said electric current flow path A has a resistance lower than the resistance of another electric current flow path B extending between said electroconductive member and the ground by way of said electron source or said drive circuit,

914
Cont.
31

said image-forming member is arranged opposite to said electron source and said electroconductive member is arranged on a substrate side of said envelope where said electron source is arranged, and

said image-forming member has an accelerator electrode for accelerating the electrons emitted from said electron source and a voltage applying terminal of said accelerator electrode is drawn out of said envelope through a substrate side thereof where said image-forming member is arranged.

9 7
17. (Amended) An image-forming apparatus according to claim 14 said accelerator electrode and the side through which it is drawn out.

10 9
18. (Amended) An image-forming apparatus according to claim 17, wherein said electroconductive member is arranged proximate to where said voltage applying terminal of said accelerator electrode is drawn out with said insulator disposed therebetween.

12
19. (Amended) An image-forming apparatus comprising:
an envelope;
an electron source and an image-forming member arranged within said envelope;
an electron source drive circuit;
an electroconductive member arranged on an inner wall surface of said envelope between said electron source and said image forming member; and

an electric circuit flow path A extending between said electroconductive member and the ground passing through said electron source and said drive circuit, wherein

Concld
Gf
B1
said electric current flow path A has a resistance lower than the resistance of another electric current flow path B extending between said electroconductive member and the ground by way of said electron source or said drive circuit,

said image-forming member is arranged opposite to said electron source and said electroconductive member is arranged on a substrate side of said envelope where said electron source is arranged, and

wherein said envelope carries an anti-charge film arranged on said inner wall surface thereof.

20. (Not Amended) An image-forming apparatus according to claim 19, wherein said anti-charge film is electrically connected to said electroconductive member.

21.¹⁴ (Amended) An image-forming apparatus, comprising

an envelope:

an electron source and an image-forming member arranged within said

envelope,
an electron source drive circuit;

an electroconductive member arranged on an inner wall surface of said envelope between said electron source and said image-forming member, and

an electric circuit flow path A extending between said
electroconductive member and the ground passing through said electron source and drive circuit,
wherein

said electric current flow path A has a resistance lower than the
resistance of another electric current flow path B extending between said electronconductive
member and the ground by way of said electron source or said drive circuit,

said image-forming member is arranged opposite to said electron
source and said electroconductive member is arranged on a substrate side of said envelope where
said electron source is arranged, and

said envelope carries an electroconductive film having a sheet
resistance between $10^8 \Omega/\square$ and $10^{10} \Omega/\square$ on said inner wall surface thereof.

¹⁵
~~22.~~ (Amended) An image-forming apparatus according to claim ¹⁴~~21~~,
wherein said electroconductive film is electrically connected to said electroconductive member.

¹⁴
^{1 3 5 6 7 11 12 14}
~~23.~~ (Amended) An image-forming apparatus according to any one of
claims ~~1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22~~ and ~~21~~, wherein said electric current flow path A has a resistant not
greater than 1/10 of the resistance of said electric current flow path B.

24. Cancelled.

25. Cancelled.